



luceo link LV

Specification Sheet



Communications	4G CAT-M1 Wi-Fi Bluetooth LE
Antenna	Internal External (optional)
Out of Power Notification	Yes
Accuracy	Class 1 (1%)
CTs	Split Core Solid Core Rogowski Coil
Metered Data	Active Power Voltage Frequency Reactive Power Current
Neutral Impedance Calculation	Yes
Power Quality Checks	Harmonics Swell Sag Power Factor
Circuits Monitored	2
Relay Drive	1
Protection	10 A C-curve circuit breaker (internal)
Remote Firmware Update	Yes
Dimensions	90mm x 92mm x 175mm (w x d x h)
Warranty	24 Months
Design Life	10 Years
Temperature Rating	-25°C to +60°C (operational) -40°C to +70°C (storage)
IP Rated	IP65
UV Rated	Yes
Compliance	IEC 61010-1:2010 AMD1:2016 Safety requirements for electrical equipment for measurement, control and laboratory use EN 61326-1:2013 Electrical equipment for measurement, control and laboratory use – EMC requirements EMC – CISPR 32, RDO – AS/NZS 4268 RDO – EN 301 908-1, EMR – ARPANSA RPS S-1, SAF – IEC 62368-1 and A2LA, TEL – AS/CA S042

